

WKPKSP 800/500



Road marking truck

WKPKSP 800/500

Machine type	Road marking truck WKPKSP 800/500
Truck type	MAN TGL 12.180
Wheel base	4500 mm
Line guide	connected to steering, pneumatic lifting
Hydraulic powerstation	Kubota Diesel engine, 24 kW at 2000 rpm, watercooled
Compressor	Boge screw type compressor, mechanically driven by poly-v-belt, effective air supply 1150 l/min at 7 bar
Glass bead pressure tank	1x 500 ltr., 1x 230 ltr.
Equipment	highsolid- and waterbased paint and 2-component cold sprayplasik system
Paint container	2x 400 ltr, pressureless, stainless steel
Rinsing fluid container	approx. 50 ltr, stainless steel
Container for liquid hardener	approx. 50 ltr, stainless steel
Twin paint pump system	two Airless pumps, each 180 ccm displaced volume, hydraulically driven, seperate injection of hardener
Spraying head	airless 2-component spraying head
Equipment	2-component coldplastic for Agglomerat- and Spotflex marking
Paint pressure container	540 ltr
Outrigger / marker units	right and left hand side, 600 mm hydraulic side access, pneumatic lifting, adjustable from operators section
Operators section	right and left, near outrigger, for operation of the machine, all necessary instruments are clearly arranged
Empty- / total weight	approx. 8050 kg / 11990 kg
Dimensions Length x width x height	approx. 8,80 m x 2,30 m x 2,85 m (without wind deflector)

Technical modifications and errors excepted, illustrations similar resp. partly including special accessories.

State of art: 24.04.2018_en