

WKP 251 GTLR



Road marking machine for cold plastic

WKP 251 GTLR

Machine Type	Road marking machine WKP 251 GTLR
Engine	Kubota V1505T, 40,8 HP (30 kW)
Fuel	diesel, capacity 55 liter
Electrical system	12 V, battery 66 Ah
Steering	strong standard mechanical steering, on request hydraulic assisted steering / hydraulic
Drive / brake system	hydrostatic drive, also acting as service brake, parking brake hydraulically controlled multi disc brake
Wheels	front: 21×8 – 9, 5 hole-rim / rear: 21×8 – 9, 5 hole-rim
Compressor	Boge screw type compressor, mechanically driven by poly-v-belt, effective air supply 1150 l/min
Operating air pressure	7 bar, silenced safety valve
Paint pressure tank	420 ltr., with agitator, other container capacities on request
Mixing-system	98 : 2, fluid or powder, static mixer on request
Marker unit	screed box for solid line
Additional equipment	on request, agglomerate and profile
Glass bead equipment	on request, metering bead dispenser up to 300 mm
Empty- / total weight	approx. 1600 kg / 2600 kg
Dimensions Length x width x height	approx. 4,00 m x 1,15 m x 1,80 m (without equipment)

Technical modifications and errors excepted,
illustrations similar resp. partly including special accessories.

State of art: 01.11.2014_en