

WTS 251 GTLR



Road marking machine for hot sprayplastic

WTS 251 GTLR

Machine Type	Road marking machine WTS 251 GTLR
Engine	Kubota V1505T, 40,8 HP (30 kW)
Fuel	diesel, capacity 55 liter
Electrical system	12 V, battery 66 Ah
Steering	strong standard mechanical steering, on request hydraulic assisted steering / hydraulic
Drive / brake system	hydrostatic drive, also acting as service brake, parking brake hydraulically controlled multi disc brake
Wheels	front: 21×8 – 9, 5 hole-rim / rear: 21×8 – 9, 5 hole-rim
Compressor	Boge screw type compressor, mechanically driven by poly-v-belt, effective air supply 1150 l/min
Operating air pressure	7 bar, silenced safety valve
Material pressure container	360 ltr., with agitator, oil burner heating
Atomizing air heating	innovative atomizing air heating integrated in thermal oil jacket of the container, 150°C – 175°C
Marker unit	adjusting spindle with outrigger and wheel
Glass bead equipment	glass bead gun
Empty- / total weight	approx. 2100 kg / 3500 kg
Dimensions Length x width x height	approx. 4,73 m x 1,15 m x 2,20 m (without equipment)

Technical modifications and errors excepted,
illustrations similar resp. partly including special accessories.

State of art: 01.11.2014_en