

WPT 251 GTLR Kombi



Road marking machine for paint and thermoplastic

WPT 251 GTLR Kombi

Machine Type	Road marking machine WPT 251 GTLR
Engine	Kubota V1505T, 40,8 HP (30 kW)
Fuel	diesel, capacity 55 liter
Electrical system	12 V, battery 66 Ah
Steering	strong standard mechanical steering, on request hydraulic assisted steering / hydraulic steering
Drive / brake system	hydrostatic drive, also acting as service brake, parking brake hydraulically controlled multi disc brake
Wheels	front: 21×8 – 9, 5 hole-rim / rear: 21×8 – 9, 5 hole-rim
Compressor	Boge screw type compressor, mechanically driven by poly-v-belt, effective air supply 1150 l/min
Operating air pressure	7 bar, silenced safety valve
Paint pressure tank	240 ltr., with hydraulic driven agitator
Marker unit	on request, two units discless
Additional equipment	on request, hand held spray gun
Glass bead equipment	on request, metering bead dispenser up to 30 cm
Thermoplastic container	220 ltr., with hydraulic driven agitator, other container capacities on request
Thermal oil heating	gas with thermostatic adjustment
Marker unit	screed box
Additional equipment	on request, profiles- or structure markings
Glass bead equipment	on request, metering bead dispenser up to 30 cm
Empty- / total weight	approx. 1700 kg / 2600 kg
Dimensions Length x width x height	approx. 4,40 m x 1,15 m x 1,80 m (without equipment)

Technical modifications and errors excepted,
illustrations similar resp. partly including special accessories.

State of art: 01.11.2014_en