

WKSP 251 light



Road marking machine for cold sprayplastic

WKSP 251 light

Machine Type	Road marking machine WKSP 251 light
Engine	Kubota D1803, 30 HP (22 kW)
Fuel	diesel, capacity 34 liter
Electrical system	12 V, battery 66 Ah
Steering	strong standard mechanical steering
Drive / brake system	hydrostatic drive, also acting as service brake, parking brake hydraulically controlled multi disc brake
Wheels	front: 6.00-9 12PR, 5 hole-rim / rear: 6.00-9 12PR, 5 hole-rim
Compressor	2-cylinder Boge compressor Typ SK 26, effective air supply 1060 l/min, mechanically driven by poly-v-belt
Operating air pressure	7 bar, silenced safety valve
Paint container unpressurized	2x 200 ltr., with agitator, other container capacities on request
Paint pump	Airless doublepump, 18 ltr/min, mixture ratio 1 : 1, 98 : 2 on request
Marker unit	units discless
Additional equipment	on request, airless hand held spray gun, external mixing
Glass bead equipment	on request, metering bead dispenser up to 300 mm
Empty- / total weight	approx. 1300 kg / 2300 kg
Dimensions Length x width x height	approx. 3,90 m x 1,25 m x 1,85 m (without equipment)
Technical modifications and errors excepted, illustrations similar resp. partly including special accessories. State of art: 01.05.2019_en	