

WKSP 251 light (98:2)



Road marking machine for cold sprayplastic

WKSP 251 light (98:2)

Machine Type	Road marking machine WKSP 251 light (98:2)
Engine	Kubota D1803, 30 HP (22 kW)
Fuel	diesel, capacity 34 liter
Electrical system	12 V, battery 66 Ah
Steering	strong standard mechanical steering
Drive / brake system	hydrostatic drive, also acting as service brake, parking brake hydraulically controlled multi disc brake
Wheels	front: 6.00-9 12PR, 5 hole-rim / rear: 6.00-9 12PR, 5 hole-rim
Compressor	2-cylinder Boge compressor Typ SK 26, effective air supply 1060 l/min, mechanically driven by poly-v-belt
Operating air pressure	7 bar, silenced safety valve
Paint pressure tank	400 ltr., with agitator, other container capacities on request
Paint pump	Airless doublepump, 16 ltr/min, mixture ratio 98 : 2
Glass bead pressure container	158 ltr. or 2x 105 ltr., with water pre separator, on request filling sieve / filling level monitor
Glass bead tank unpressurized	70 ltr.
Marker unit	units discless
Glass bead equipment	on request, metering bead dispenser up to 300 mm
Empty- / total weight	approx. 1300 kg / 2300 kg
Dimensions Length x width x height	approx. 3,90 m x 1,25 m x 1,85 m (without equipment)

Technical modifications and errors excepted,
illustrations similar resp. partly including special accessories.

State of art: 01.05.2019_en