

TOPLINER 100P



Hand-guided road marking machine

TOPLINER 100P

<

Machine Type	Hand-guided road marking machine TOPLINER 100P
Engine	Honda-GX 390, 11,7 hp (8,7 kW)
Fuel	gasoline, capacity 6,1 liter
Electrical system	12 V, battery 30 Ah, e-start
Steering	swivel wheel with attached parking brake
Drive / brake system	hydrostatic and differential gear axle
Wheels	front: pneumatic tyre 4.00×8 4PR / rear: solid rubber wheel d=200 mm
Compressor	Atlas Copco LE 40/10, effective air supply 700 ltr./min.
Operating air pressure	6,4 bar, silenced safety valve
Paint pressure tank	on request 48 or 65 ltr., with agitator
Marker unit	on request, rolling disc marker unit or without rolling discs
Additional equipment	electronic skip line control, hand held spray gun with hose set, special equipment on request
Glass bead equipment	25 ltr. bead tank and bead gun 10-30 cm dispensing width
Empty weight	approx. 310 kg
Dimensions Length x width x height	approx. 1,90 m x 0,75 m x 1,20 m (without glass bead tank)

Technical modifications and errors excepted,
illustrations similar resp. partly including special accessories.

State of art: 29.03.2017_en