

LineLazer 5900



**Hand-guided road marking machine
with approved piston pump technique for processing of road marking paint
including waterborne paint which is suitable for airless processing**

LineLazer 5900

Optional designs

STANDARD

LiveLook-Display with SmartControl
electronic spray pressure control, logging of all
important jobsite data, digital display of main operating
parameters

DualComfort-Handle Bar System
fits all users – easy to adjust

EZ-Align-Front Wheel System
for straight line tracking, intuitive design

EasyMark-Gun Adjustment System

HP AUTOMATIC

– includes all features of the Standard series, PLUS:

Automatic- and Semi-Automatic gun(s)

Auto-Layout II
easy to use, cuts layout time in half, works directly from
the gun

Data Logging with J-Log System
on-board job information for „proof“ of completion

On-board power via 12V battery

Technical Data

Machine Type

Hand-guided road marking machine LineLazer 5900

Engine	Honda-gasoline engine GX 160
Pump capacity	max. 6.0 l/min.
Operating pressure	max. 227 bar
Nozzle size	max. 0.043“ (1 gun), max. 0,029“ (2 guns)
Steering	swivel wheel, lockable with hand lever
Scope of supply	1 spray gun, 15 m spray hose, tip guard, spray nozzles LL5319 and LL5321, plastic paint pail, capacity ca. 19 litres, with cover
Additional equipment	2. spray gun for double lines, wide-line unit, line pointer, 60 ltr. paint container, bead dispenser, Satellit, LineDriver etc.
Empty weight	STANDARD: approx. 113 kg / HP AUTOMATIC: approx. 121 kg
Dimensions Length x width x height	approx. 1.75 m x 0.87 m x 1.13 m

Technical modifications and errors excepted,
illustrations similar resp. partly including special accessories.

State of art: 23.09.2018_en

We are authorized Graco distributor!