

WTE 850



Road marking machine for thermoplastic with extruder

WTE 850**Machine Type****Road marking machine WTE 850**

Engine	Kubota V3307, 3331 ccm, 70 HP (51 kW), at 2000 r/min
Fuel	diesel, capacity 100 liter
Electrical system	12 V, battery 100 Ah
Steering	strong standard mechanical steering, on request hydraulic assisted steering / hydraulic
Drive / brake system	hydrostatic drive, also acting as service brake, parking brake hydraulically controlled multi disc brake, on request 2-stage-drive
Wheels	front: 185 R 14 – 5-hole-rim / rear: 225 R 15 – 6-hole-rim
Compressor	screw type compressor, hydraulically driven, air supply 1850 l/min
Operating air pressure	7 bar self-adjusting, safety valve 8,5 bar
Thermoplastic container	400 ltr., with agitator, other container capacities on request
Thermal oil heating	on request gas / diesel
Glass bead pressure container	2x 230 ltr., with water pre separator, on request filling sieve / filling level monitor
Extruder	automatic thickness control, different flap sizes available
Additional equipment	on request, quick cleaning system for extruder head
Glass bead equipment	on request, metering bead dispenser up to 30 cm
Empty- / total weight	approx. 3500 kg / 5500 kg
Dimensions Length x width x height	approx. 5,50 m x 1,20 m x 2,60 m (without equipment)

Technical modifications and errors excepted,
illustrations similar resp. partly including special accessories.

State of art: 11.03.2015_en