

WKSP 850 (1:1)



Road marking machine for cold sprayplastic

WKSP 850 (1:1)

Machine Type

Road marking machine WKSP 850 (1:1)

Engine	Kubota V3307, 3331 ccm, 70 HP (51 kW), at 2000 r/min
Fuel	diesel, capacity 100 liter
Electrical system	12 V, battery 100 Ah
Steering	strong standard mechanical steering, on request hydraulic assisted steering / hydraulic
Drive / brake system	hydrostatic drive, also acting as service brake, parking brake hydraulically controlled multi disc brake, on request 2-stage-drive
Wheels	front: 185 R 14 – 5-hole-rim / rear: 225 R 15 – 6-hole-rim
Compressor	screw type compressor, hydraulically driven, driving speed adjustable, air supply 600 up to 1850 l/min
Operating air pressure	7 bar self-adjusting, safety valve 8,5 bar
Paint container unpressurized	2x 500 ltr., with agitator, other container capacities on request
Paint pump	Airless double pump, 22 ltr/min, mixture ratio 1 : 1, 98 : 2 on request
Glass bead pressure container	2x 230 ltr., with water pre separator, on request filling sieve / filling level monitor
Marker unit	units discless
Additional equipment	on request, airless hand held spray gun, external mixing
Glass bead equipment	on request, metering bead dispenser up to 30 cm
Empty- / total weight	approx. 3500 kg / 5500 kg
Dimensions Length x width x height	approx. 5,50 m x 1,20 m x 2,60 m (without equipment)

Technical modifications and errors excepted, illustrations similar resp. partly including special accessories.

State of art: 01.11.2014_en