

WKSP 351 GTLR



Road marking machine for cold sprayplastic

WKSP 351 GTLR

Machine Type	Road marking machine WKSP 351 GTLR
Engine	Perkins 404F-E22TA, 58,5 HP (43 kW), at 2400 r/min
Fuel	diesel, capacity 50 liter
Electrical system	12 V, battery 88 Ah
Steering	strong standard mechanical steering, on request hydraulic assisted steering / hydraulic
Drive / brake system	hydrostatic drive, also acting as service brake, parking brake hydraulically controlled multi disc brake
Wheels	front: 21x8 – 9, 5 hole-rim / rear: 6.50-10PR, 5 hole-rim
Compressor	Boge screw type compressor, mechanically driven by poly-v-belt, effective air supply 1500 or 2300 l/min
Operating air pressure	7 bar, automatically controlled
Paint container unpressurized	2x 200 ltr., with agitator, other container capacities on request
Paint pump	Airless doublepump, 18 ltr/min, mixture ratio 1 : 1, 98 : 2 on request
Glass bead pressure container	158 ltr. or 2x 105 ltr., with water pre separator, on request filling sieve / filling level monitor
Glass bead tank unpressurized	on request, 300 ltr.
Marker unit	units discless
Additional equipment	on request, airless hand held spray gun, external mixing
Glass bead equipment	on request, metering bead dispenser up to 300 mm
Empty- / total weight	approx. 2500 kg / 3800 kg
Dimensions Length x width x height	approx. 5,16 m x 1,20 m x 2,52 m (without equipment)

Technical modifications and errors excepted, illustrations similar resp. partly including special accessories.

State of art: 07.10.2016_en