

Infrared heating units



For fast, gentle heating of asphalt surfaces and seams

- Only full-metal, stainless steel radiant heater devices. The heaters can be disabled individually to change the size of the heated area.
- Using an 11-stage-gas-regulator, the heat output can be adjusted from 0.4 to 1.5 bar.

- The units can also be equipped with a regulator and battery power.
The surface temperature of the asphalt is depending on the set temperature.

Infrared heating units

Technical details:

Description	AHG 15/75	AHG 30/150	AHG 30/200
Item no.	5115 0000	5117 0000	5118 0000
Frame	Without bottle platform, with 4 adjustable feet	With bottle holder for 2 gas bottles with wheels	With bottle holder for 2 gas bottles with wheels
Approx. heating area	150 x 750 mm	300 x 1500 mm	300 x 2000 mm
Max. heating power	11 kW	40 kW	50 kW
Approx. length	840 mm	2150 mm	2650 mm
Approx. width	200 mm	860 mm	860 mm
Approx. deadweight	9 kg	95 kg	110 kg

Accessories:

Electric temperature control	no	Item no. 5090 9000	Item no. 5090 9000
Power supply unit	no	Item no. 5090 9100	Item no. 5090 9100

Description	AHG 90/100	AHG 120/125
Item no.	5089 0000	5120 0000
Frame	With bottle holder for 2 gas bottles 2 fixed castors 2 swivel castors	With bottle holder for 2 gas bottles 2 fixed castors 2 swivel castors
Approx. heating area	900 x 100 mm	1200 x 1250 mm
Max. heating power	78 kW	126 kW
Approx. length	1350 mm	1800 mm
Approx. width	1180 mm	1740 mm
Approx. deadweight	141 kg	202 kg

Accessories:

Electric temperature control	Item no. 5090 9000	Item no. 5090 9000
Power supply unit	Item no. 5090 9100	Item no. 5090 9100

Subject to technical changes.