

Mastic asphalt finisher KBR 110 SL



For automatic installation of mastic asphalt during road building with automatic grit

- The minimum installation width is 250 mm; the installation width can be increased.
- Hydrostatic chain-driven all-wheel drive, 0-3 m / min, infinitely adjustable. Max. movement speed. Equipped with pendulous suspended crawler wrappings. The height is adjusted via stacker. hydraulically driven. Standard hydraulic system.
- Finisher tools in milled design with pressing rollers. propane-heated and each screed part has a thermometer for temperature control.
- Grit spreading is computer-controlled.

- There is an option to equip the screed with
 - Blade distributor
 - 230 V generator
 - Fold-out caterpillar
 - Replaceable end fittings
 - Levelling
 - Hydraulic pillar chaser
 - Assembly jig

Mastic asphalt finisher KBR 110 SL

Technical details:

Description	KBR 110 SL
Installation width	3250 mm – 12,500 mm
Height adjustment finisher section	from +100 mm to -350 mm
Heating of finisher section	Propane gas bar burner made of stainless steel
Drive motor	HATZ diesel engine type 4L41C, sound-insulated
Traction drive	Hydrostatic all-wheel drive, reversible with pendulous susp. caterpillar drives
Operating speed:	0.25 – 3.00 m/min
Dimensions of basic unit:	
Approx. length	4000 mm
Approx. width	2950 mm
Approx. height	2700 mm
Approx. installation width	3250 mm
Approx. weight	7800 kg

Subject to technical changes.