

Mastic asphalt finisher KBR 75 SL



For automatic installation of mastic asphalt for road building with automatic grit

- The minimum installation width is 2500 mm. The installation width can be increased.
- Hydrostatic chain-driven all-wheel drive. Speed 0-3 m / min, infinitely adjustable. Max. 1000 kg. Can be equipped with vulcollan wrapping on the chassis. The height is adjusted with stable elevating system, hydraulically driven. Standard hydraulically adjustable.
- Finisher tools in milled design with pressing rollers. propane-heated and each screed part has a thermometer for temperature control.
- Grit spreading computer

- There is an option to equip the finisher with:
 - Blade distributor
 - Distribution screed
 - Road chassis from 20 t
 - Replaceable end fittings
 - Hydraulic pillar chassis
 - assembly jig

Mastic asphalt finisher KBR 75 SL

Technical details:

Description	KBR 75 SL
Installation width	2500 mm – 8500 mm
Height adjustment finisher section	from +100 mm to -250 mm
Heating for finisher section	Propane gas bar burner made of stainless steel
Drive motor	HATZ diesel engine type 2L41C, 24 kW sound-insulated
Traction drive	Hydrostatic all-wheel drive, reversible with vulcollan wrapping
Operating speed	0.25 – 3.00 m/min
Dimensions of basic unit:	
Approx. length	3250 mm
Approx. width	2450 mm
Approx. height	1900 mm
Approx. installation width	2500 mm
Approx. weight	5800 kg

Subject to technical changes.