

Mastic asphalt transportable boiler 5.000 to 11.000 l



Special equipment for transporting mastic asphalt and mastic

- Boiler capacity from 5.000 to 11.000 l
- Boiler shell, front walls and agitating arms and heat-resistant steel
- Direct hydraulic agitator drive with variable speed operated valve
- Hatz diesel engine in sound enclosure
- All-round boiler insulation with 60 mm rock wool made of highly polished stainless steel
- Agitating hands are made of durable steel

- Propane gas or fully automatic
The boiler is protected by a large flame tu
and a temperature li
- The boilers can be mounted on trucks, trai
having
sufficient loading ca
- This series is characterized by its low deac
with low total height, short design, powerful
cock.

Mastic asphalt transportable boiler 5.000 to 11.000 l

Technical details:

Description	RGTK 5000	RGTK 6000	RGTK 9000
Item no. RGTK Gas	82050 0100	82060 0100	82090 0100
Item no. RGTK oil	82050 0000	82060 0000	82090 0000
Boiler capacity	5.0 m ³	6.0 m ³	9.0 m ³
Approx. bearing length	3.390 mm	3.790 mm	4.990 mm
Approx. width	2.200 mm	2.200 mm	2.200 mm
Approx. height	2.200 mm	2.200 mm	2.200 mm
Filling lid	1.300 x 800 mm	1.300 x 800 mm	1.300 x 800 mm
Drain cock	600 x 360 mm	600 x 360 mm	600 x 360 mm
Approx. deadweight	4.100 kg	4.400 kg	5.300 kg
Diesel engine power	24.4 kW	24.4 kW	36.7 kW
Max. Torque (agitator)	20.000 Nm	40.000 Nm	40.000 Nm
Description	RGTK 10000	RGTK 11000	
Item no. RGTK Gas	82100 0100	82110 0100	
Item no. RGTK oil	82100 0000	82110 0000	
Boiler capacity	10.0 m ³	11.0 m ³	
Approx. bearing length	5.390 mm	5.790 mm	
Approx. width	2.200 mm	2.200 mm	
Approx. height	2.200 mm	2.200 mm	
Filling lid	1.300 x 800 mm	1.300 x 800 mm	
Drain cock	600 x 360 mm	600 x 360 mm	
Approx. deadweight	5.700 kg	6.000 kg	
Diesel engine power	36.7 kW	36.7 kW	
Max. Torque (agitator)	40.000 Nm	40.000 Nm	

Subject to technical changes.