

TOPLINER 100KP



Hand-guided road marking machine for cold plastic

TOPLINER 100KP

Machine Type	Hand-guided road marking machine TOPLINER 100KP
Engine	Honda-GX 390, 11,7 hp (8,7 kW)
Fuel	gasoline, capacity 6,1 liter
Electrical system	12 V, battery 30 Ah, e-start
Steering	swivel wheel with attached parking brake
Drive / brake system	hydrostatic and differential gear axle
Wheels	front: pneumatic tyre 4.00x8 4PR / rear: solid rubber wheel d=200 mm
Compressor	effective air supply 798 ltr./min.
Operating air pressure	6,4 bar, silenced safety valve
Mixing-system	98 : 2, fluid, static mixer
Pressure tank main component	approx. 48 ltr.
Hardener pump	0,02 – 1,5 ltr./min.
Pressure tank hardener	approx. 2 ltr.
Additional equipment	electronic skip line control on request
Glass bead equipment	25 ltr. bead tank and bead gun 10-30 cm dispensing width
Empty weight	approx. 400 kg
Dimensions Length x width x height	approx. 1,90 m x 0,75 m x 1,20 m (without bead tank)

Technical modifications and errors excepted,
illustrations similar resp. partly including special accessories.

State of art: 03.04.2016_en