

WKPKSP 850



Road marking machine for cold plastic

WKPKSP 850

Machine Type

Road marking machine WKPKSP 850

Engine	Kubota V3307, 3331 ccm, 70 HP (51 kW), at 2000 r/min
Fuel	diesel, capacity 100 liter
Electrical system	12 V, battery 100 Ah
Steering	strong standard mechanical steering, on request hydraulic assisted steering / hydraulic
Drive / brake system	hydrostatic drive, also acting as service brake, parking brake hydraulically controlled multi disc brake, on request 2-stage-drive
Wheels	front: 185 R 14 – 5-hole-rim / rear: 225 R 15 – 6-hole-rim
Compressor	screw type compressor, hydraulically driven, driving speed adjustable, air supply 600 up to 1850 l/min
Operating air pressure	7 bar self-adjusting, safety valve 8,5 bar
Paint pressure tank	540 ltr., with hydraulically driven agitator, other container capacities on request
Mixing-system	98 : 2, fluid hardener pump with static mixer
Paint container unpressurized	2x 200 ltr., with agitator, other container capacities on request
Paint pump	Airless doublepump, 22 ltr/min, mixture ratio 1 : 1
Glass bead pressure container	2x 230 ltr., with water separator, on request filling sieve / filling level monitor
Marker unit	on request, Visi-Dot / Visi-Struct / screed box / profile
Additional equipment	on request, hydraulic lifted line guide
Glass bead equipment	on request, metering bead dispenser up to 30 cm
Empty- / total weight	approx. 3500 kg / 5500 kg
Dimensions Length x width x height	approx. 5,50 m x 1,20 m x 2,60 m (without equipment)

Technical modifications and errors excepted, illustrations similar resp. partly including special accessories.

State of art: 08.10.2016_en