

WKSP 1001 (98:2)



Road marking machine for cold sprayplastic

WKSP 1001 (98:2)

Machine Type

Road marking machine WKSP 1001 98:2

Engine	Hatz 4H50TIC, 1952 ccm, 73,4P (54 kW), at 2800 r/min
Fuel	diesel, capacity 105 liter
Electrical system	12 V, battery 90 Ah
Steering	strong standard mechanical steering, on request hydraulic steering
Drive / brake system	hydrostatic drive, also acting as service brake, parking brake hydraulically controlled multi disc brake
Wheels	front: 195/70 R15 – 5-hole-rim / rear: 215/70 R14 – 6-hole-rim
Compressor	Boge screw type compressor Typ CM32, effective air supply 2400 l/min, mechanically driven by poly-v-belt
Operating air pressure	7 bar, silenced safety valve
Paint pressure tank	front: 400 ltr. / rear: 400 ltr., with agitator, other container capacities on request
Paint pump	Airless doublepump, 22 ltr/min, mixture ratio 98 : 2
Marker unit	units discless
Glass bead equipment	on request, metering bead dispenser up to 300 mm
Empty- / total weight	approx. 3000 kg / 5800 kg
Dimensions Length x width x height	approx. 5,50 m x 1,50 m x 2,20 m (without equipment)

Technical modifications and errors excepted,
illustrations similar resp. partly including special accessories.

State of art: 03.10.2016_en